

<b>ASHLAND</b> <sup>®</sup>	Page: 1 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

Conforms to EU Regulation 1907/2006/EC as amended. - SDSCLP\_GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Derakane™ 470HT-400  
RESIN  
™ Trademark, Ashland or its subsidiaries, registered in various countries

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Reserved for industrial and professional use.

<b>1.3 Details of the supplier of the safety data sheet</b>  Ashland P.O. Box 8619 NL3009 AP, Rotterdam Netherlands  EUSMT@ashland.com	<b>1.4 Emergency telephone number</b>  00-800-274-5263-3/001-606-329-5701 , or contact your local emergency telephone number at 112  <b>Product Information</b> +31 10 497 5000 (in the Netherlands), or contact your local CSR contact person
---	---

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (67/548/EEC, 1999/45/EC)


Flammable	R10: Flammable.
Harmful	R20: Harmful by inhalation.
	R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Irritant	R36/37/38: Irritating to eyes, respiratory system and skin.

### 2.2 Label elements

#### Labelling according to EC Directives(1999/45/EC)

<b>ASHLAND</b> <sup>®</sup>	Page: 2 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

Hazard symbols :



Harmful

R-phrases :

R10  
R20  
R36/37/38  
  
R48/20

Flammable.  
Harmful by inhalation.  
Irritating to eyes, respiratory system and skin.  
Harmful: danger of serious damage to health by prolonged exposure through inhalation.

S-phrases :

S16  
  
S23  
S26  
  
S37/39  
  
S51  
S43

Keep away from sources of ignition - No smoking.  
Do not breathe gas/fumes/vapour/spray.  
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Wear suitable gloves and eye/face protection.  
Use only in well-ventilated areas.  
In case of fire, use foam, carbon dioxide (CO<sub>2</sub>), Water spray, dry chemical.

Hazardous components which must be listed on the label:  
100-42-5 Styrene

### 2.3 Other hazards

Assessment : PBT substance , vPvB substance - not determined

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Static Accumulator

#### Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Styrene	100-42-5 202-851-5 01-2119457861-32-xxxx	R10 Xn; R20 Xi; R36/37/38	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315	>= 25 - < 40

<b>ASHLAND®</b>		Page: 3 of 19
		Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>		Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605		MSDS Number: R0402451 Version: 3.0

		Xn; R48/20 Xn; R65	Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 1; H372 Asp. Tox. 1; H304	
Methacrylic acid	79-41-4 201-204-4	Xn; R21/22 C; R35	Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1A; H314	>= 2,5 - < 5
Tetramethylammonium chloride	75-57-0 200-880-8	Xi; R36/37/38 T; R25 T; R24	Acute Tox. 3; H301 Acute Tox. 3; H311 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	>= 0,1 - < 0,5
Hydroquinone	123-31-9 204-617-8	Carc.Cat.3; R40 Mut.Cat.3; R68 Xn; R22 Xi; R41 R43 N; R50 Carc.Cat.3; R40 Mut.Cat.3; R68	Acute Tox. 4; H302 Skin Sens. 1; H317 Muta. 2; H341 Carc. 2; H351 Aquatic Acute 1; H400 Eye Dam. 1; H318	>= 0 - < 0,1

For the full text of the R-phrases mentioned in this Section, see Section 16.  
For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.  
If symptoms persist, call a physician.  
In case of shortness of breath, give oxygen.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off immediately with plenty of water.  
If skin irritation persists, call a physician.
- In case of eye contact : Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.  
Remove contact lenses.

<b>ASHLAND</b> <sup>®</sup>		Page: 4 of 19
		Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>		Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605		MSDS Number: R0402451 Version: 3.0

If swallowed : Do not induce vomiting without medical advice.  
Never give anything by mouth to an unconscious person.  
Consult a physician if necessary.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)  
central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects  
Lack of coordination  
confusion  
liver damage

Risks : This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : no data available

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Dry chemical  
Carbon dioxide (CO<sub>2</sub>)  
Foam  
Water spray

Unsuitable extinguishing media : Halons  
High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not use a solid water stream as it may scatter and spread fire.  
Do not allow run-off from fire fighting to enter drains or water courses.

<b>ASHLAND</b> <sup>®</sup>		Page: 5 of 19
		Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>		Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605		MSDS Number: R0402451 Version: 3.0

Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Further information : Keep containers and surroundings cool with water spray.  
Prevent fire extinguishing water from contaminating surface water or the ground water system.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.  
Ensure adequate ventilation.  
Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

no data available

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

<b>ASHLAND</b> <sup>®</sup>	Page: 6 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

Do not breathe vapours or spray mist.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Avoid exceeding of the given occupational exposure limits (see section 8).  
 Smoking, eating and drinking should be prohibited in the application area.  
 Ensure all equipment is electrically grounded before beginning transfer operations.

Advice on protection against fire and explosion : Take measures to prevent the build up of electrostatic charge. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Keep product and empty container away from heat and sources of ignition. No sparking tools should be used.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Other data : Stable under recommended storage conditions.

### 7.3 Specific end use(s)

no data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Value type	Form of Exposure	Control parameters	Update	Basis
Styrene	100-42-5	TWA		100 ppm 430 mg/m <sup>3</sup>	2007	EH40 WEL
Further information:						
Styrene	100-42-5	STEL		250 ppm 1.080 mg/m <sup>3</sup>	2007	EH40 WEL
Methacrylic acid	79-41-4	TWA		20 ppm 72 mg/m <sup>3</sup>	2007	EH40 WEL

<b>ASHLAND®</b>	Page: 7 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

Methacrylic acid	79-41-4	STEL	40 ppm 143 mg/m3	2007	EH40 WEL
Hydroquinone	123-31-9	TWA	0,5 mg/m3	2007	EH40 WEL

DNEL

Styrene	: End Use: <b>Workers</b> Exposure routes: <b>Inhalation</b> Potential health effects: <b>Short-term exposure, Systemic effects</b> Value: <b>289 mg/m3</b>
Styrene	: End Use: <b>Workers</b> Exposure routes: <b>Inhalation</b> Potential health effects: <b>Short-term exposure, Local effects</b> Value: <b>306 mg/m3</b>
Styrene	: End Use: <b>Workers</b> Exposure routes: <b>Inhalation</b> Potential health effects: <b>Long-term exposure, Systemic effects</b> Value: <b>85 mg/m3</b>
Styrene	: End Use: <b>Workers</b> Exposure routes: <b>Skin contact</b> Potential health effects: <b>Long-term exposure, Systemic effects</b> Value: <b>406 mg/kg</b>
Styrene	: End Use: <b>Consumers</b> Exposure routes: <b>Inhalation</b> Potential health effects: <b>Short-term exposure, Systemic effects</b> Value: <b>174,25 mg/m3</b>
Styrene	: End Use: <b>Consumers</b> Exposure routes: <b>Inhalation</b> Potential health effects: <b>Short-term exposure, Local effects</b> Value: <b>182,75 mg/m3</b>
Styrene	: End Use: <b>Consumers</b> Exposure routes: <b>Skin contact</b> Potential health effects: <b>Long-term exposure, Systemic effects</b> Value: <b>343 mg/kg</b>
Styrene	: End Use: <b>Consumers</b> Exposure routes: <b>Ingestion</b>

<b>ASHLAND</b> <sup>®</sup>	Page: 8 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

<b>Styrene</b>	Potential health effects: Long-term exposure, Systemic effects Value: 2,1 mg/kg : End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term exposure, Systemic effects Value: 10,2 mg/m3
----------------	--

## 8.2 Exposure controls

### Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below level of overexposure (from known, suspected or apparent adverse effects).

### Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Hand protection : Wear resistant gloves such as:  
Polyvinyl alcohol or nitrile- butyl-rubber gloves
- Eye protection : Safety glasses with side-shields
- Skin and body protection : Wear as appropriate:  
Safety shoes  
Flame-resistant clothing
- Hygiene measures : Keep away from food, drink and animal feedingstuffs.  
When using do not eat, drink or smoke.  
Ensure that eyewash stations and safety showers are close to the workstation location.

### Environmental exposure controls

- General advice : Prevent further leakage or spillage if safe to do so.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : yellow
- Odour : pungent



<b>ASHLAND</b> <sup>®</sup>	Page: 9 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

Odour Threshold : no data available  
 pH : no data available  
 Freezing point / Melting point : no data available  
 Boiling point : 145 °C  
 Flash point : 26,11 °C; Pensky Martens closed cup  
 Evaporation rate : no data available  
 Flammability (solid, gas) : no data available  
 Burning rate : no data available  
 Lower explosion limit : 1 %(V)  
 Upper explosion limit : 6 %(V)  
 Vapour pressure : 6,00 hPa; 20,00 °C  
 Relative vapour density : > 1; AIR=1  
 Relative density : +/- 0.14 1,1275; 20,00 °C  
 Density : +/- 0.14 1,1275 g/cm<sup>3</sup>; 20,00 °C  
 Water solubility : insoluble  
 Solubility in other solvents : no data available  
 Partition coefficient: n-octanol/water : no data available  
 Auto-ignition temperature : 490 °C  
 Ignition temperature : no data available  
 Thermal decomposition : no data available  
 Viscosity, dynamic : no data available  
 Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s; 40 °C

<b>ASHLAND</b> <sup>®</sup>		Page: 10 of 19
		Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>		Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605		MSDS Number: R0402451 Version: 3.0

Explosive properties : no data available

Oxidizing properties : no data available

## 9.2 Other information

Bulk density : no data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Hazardous polymerisation may occur.  
Vapours may form explosive mixture with air.

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Further information: Stable under recommended storage conditions.

: Hazardous polymerisation may occur.  
Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Exposure to sunlight.  
Exposure to air.

### 10.5 Incompatible materials

Materials to avoid : Acids  
alkalis  
aluminum  
aluminum chloride  
Bases  
Copper  
Copper alloys  
halogens  
iron chloride  
metal salts  
Peroxides  
Amines  
Oxidizing agents

### 10.6 Hazardous decomposition products

<b>ASHLAND</b> <sup>®</sup>	Page: 11 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

Hazardous decomposition products : carbon dioxide and carbon monoxide  
Hydrocarbons

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Product

- Acute oral toxicity : no data available
- Acute inhalation toxicity : no data available
- Acute dermal toxicity : no data available
- Skin corrosion/irritation : no data available
- Serious eye damage/eye irritation : no data available
- Respiratory or skin sensitisation : no data available
- STOT - repeated exposure : Target Organs: Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: mild effects on color vision, effects on hearing, respiratory tract damage (nose, throat, and airways), central nervous system effects
- Aspiration toxicity : The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### Components:

##### **Styrene :**

- Acute oral toxicity : LD 50: 2.650 mg/kg, Rat
- Acute inhalation toxicity : LC 50: 2800 ppm, 4 h, Rat,
- Acute dermal toxicity : LD 50: > 2.000 mg/kg, Rat, OECD Test Guideline 402, The substance or mixture has no acute dermal toxicity
- STOT - single exposure : Assessment: May cause respiratory irritation.

<b>ASHLAND®</b>	Page: 12 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

Further information : Central nervous system

**Methacrylic acid :**

Acute oral toxicity : LD 50: 1.320 mg/kg, Rat(male), OECD Test Guideline 401

Acute inhalation toxicity : LD 50: 7,1 mg/l, 4 h, Rat, Aerosol

Acute dermal toxicity : LD 50: 500 - 1.000 mg/kg, Rabbit

**Tetramethylammonium chloride :**

Acute oral toxicity : LD 50: 50 mg/kg, Rat

Acute dermal toxicity : LD50: 527 mg/kg, Rat

**Hydroquinone :**

Acute oral toxicity : LD 50: 320 mg/kg, Rat

Respiratory or skin sensitisation : Classification: May cause sensitization by skin contact.

Further information : Central nervous system

## SECTION 12: Ecological information

### 12.1 Toxicity

**Product:**

no data available

**Components:**

**Styrene:**

Toxicity to fish : LC 50: 4,02 mg/l, 96 h, Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates : EC 50: 4,7 mg/l, 48 h, Water flea (Daphnia magna)

<b>ASHLAND</b> <sup>®</sup>	Page: 13 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

Toxicity to algae : EC 50: > 4,9 mg/l, 72 h, *Pseudokirchneriella subcapitata* (green algae)

Toxicity to bacteria : EC 50: ca. 500 mg/l, 0,5 h, activated sludge

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,01 mg/l, 21 d, Water flea (*Daphnia magna*)

**Tetramethylammonium chloride:**

Toxicity to fish : LC 50: 462 mg/l, 96 h, *Pimephales promelas* (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates : LC 50: 55,6 mg/l, 48 h, Water flea (*Daphnia magna*)

**Hydroquinone:**

Toxicity to fish : LC 50: 0,044 mg/l, 96 h, Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC 50: 0,25 - 0,33 mg/l, 48 h, Water flea (*Daphnia magna*), static test

M-Factor : 10

**12.2 Persistence and degradability**

**Product:**

no data available

**Components:**

**Styrene :**

Biodegradability : Readily biodegradable

**12.3 Bioaccumulative potential**

**Product:**

Bioaccumulation : The bioaccumulation potential cannot be determined.

<b>ASHLAND</b> <sup>®</sup>		Page: 14 of 19
		Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>		Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605		MSDS Number: R0402451 Version: 3.0

**Components:**  
no data available

#### 12.4 Mobility in soil

**Product:**  
no data available

**Components:**  
no data available

#### 12.5 Results of PBT and vPvB assessment

**Product:**  
no data available

**Components:**  
no data available

#### 12.6 Other adverse effects

**Product:**  
no data available

**Components:**  
no data available

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Container hazardous when empty.  
Dispose of in accordance with the European Directives on waste and hazardous waste.  
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

<b>ASHLAND</b> <sup>®</sup>	Page: 15 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

---

## SECTION 14: Transport information

### 14.1 UN number

**ADR:** UN1866

**ADNR:** UN1866

**RID:** UN1866

**INTERNATIONAL MARITIME DANGEROUS GOODS:** UN1866

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:** UN1866

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** UN1866

### 14.2 UN proper shipping name

**ADR:** RESIN SOLUTION

**ADNR:** RESIN SOLUTION

**RID:** RESIN SOLUTION

**INTERNATIONAL MARITIME DANGEROUS GOODS:** RESIN SOLUTION

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:** Resin solution

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** Resin solution

### 14.3 Transport hazard class(es)

**ADR:** 3

**ADNR:** 3

**RID:** 3

**INTERNATIONAL MARITIME DANGEROUS GOODS:** 3

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:** 3

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** 3

### 14.4 Packing group

**ADR:** III

**ADNR:** III

**RID:** III

**INTERNATIONAL MARITIME DANGEROUS GOODS:** III

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:** III

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** III

### 14.5 Environmental hazards

**ADR:** not applicable

**ADNR:** not applicable

**RID:** not applicable

**INTERNATIONAL MARITIME DANGEROUS GOODS:** not applicable

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:** not applicable

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** not applicable

<b>ASHLAND</b> <sup>®</sup>	Page: 16 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Ship Type: Not applicable

Hazard code(s): Not applicable

Pollutant Category: Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Hazard class	Number	Quantity 1	Quantity 2
Flammable.	6	5.000 t	50.000 t

#### Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	q (quantity restricted)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)
Japan. Kashin-Hou Law List	y (positive listing)
Korea. Toxic Chemical Control Law (TCCL) List	n (Negative listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	n (Negative listing)
China. Inventory of Existing Chemical Substances	y (positive listing)



<b>ASHLAND®</b>		Page: 17 of 19
		Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>		Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605		MSDS Number: R0402451 Version: 3.0

## 15.2 Chemical Safety Assessment

no data available

---

## SECTION 16: Other information

### Full text of R-phrases referred to under sections 2 and 3

R10	Flammable.
R20	Harmful by inhalation.
R21/22	Harmful in contact with skin and if swallowed.
R22	Harmful if swallowed.
R24	Toxic in contact with skin.
R25	Toxic if swallowed.
R35	Causes severe burns.
R36/37/38	Irritating to eyes, respiratory system and skin.
R40	Limited evidence of a carcinogenic effect.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50	Very toxic to aquatic organisms.
R65	Harmful: may cause lung damage if swallowed.
R68	Possible risk of irreversible effects.

### Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.
H400	Very toxic to aquatic life.

### Further information

Other information : The information accumulated herein is believed to be accurate

<b>ASHLAND</b> <sup>®</sup>	Page: 18 of 19
	Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>	Print Date: 08.08.2014
Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	MSDS Number: R0402451 Version: 3.0

but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (+31 10 497 5000).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
 BEI : Biological Exposure Index  
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
 FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level  
 ABM : Water Hazard Class for the Netherlands  
 ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.  
 ADN: Regulation for the Carriage of Dangerous Substances on the Rhine  
 CLP : Classification, Labelling and Packaging  
 CSA : Chemical Safety Assessment

<b>ASHLAND</b> <sup>®</sup>		Page: 19 of 19
		Revision Date: 02.10.2013
<b>SAFETY DATA SHEET</b>		Print Date: 08.08.2014
	Derakane™ 470HT-400 RESIN ™ Trademark, Ashland or its subsidiaries, registered in various countries 566605	

CSR : Chemical Safety Report  
 DNEL : Derived No Effect Level.  
 EINECS : European Inventory of Existing Commercial Chemical Substances.  
 ELINCS : European List of Notified Chemical Substances  
 PEC : Predicted Effect Concentration  
 PEL : Permissible Exposure Limits  
 PNEC : Predicted No Effect Concentration  
 R-phrase : Risk phrase  
 REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals  
 RID : Regulation Concerning the International Transport of Dangerous Goods by Rail  
 S-phrase: Safety phrase  
 WGK : German Water Hazard Class