

THICKENERS LINED WITH DERAKANE BASED MORTAR

Derakane Epoxy Vinyl Ester Resins – Case History



Fabricator

Produced by Wallcrete Ltd., Zambia.

Location / Year

Mining industry in Africa since 1972.

Fabrication

The **DERAKANE epoxy vinyl ester resin** was blended with specific fillers to form a corrosion resistant rapid setting polymer concrete. This system has been used for the lining of thickeners in the mining industry and applied to large surface areas of chemical and mining plants.

Service Conditions

Aggressive and corrosive conditions requiring good chemical and corrosion resistant flooring combined with excellent mechanical properties.

Last update in 1987.

NOTICE : No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN ; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



Ashland is committed to the continuous evolution of technology and service solutions that promote health, safety and environmental protection around the world. © Registered trademark and ™ trademark of Ashland Inc.
* Registered service mark of the American Chemistry Council, © 2009 Ashland
<http://www.ashland.com>, <http://www.derakane.com>